



PRODUCT DATA SHEET

MAJESTIC™ UNIVERSAL TRACTOR HYDRAULIC FLUID (UTHF)

PRODUCT DESCRIPTION

MAJESTIC™ UTHF is formulated with selected Group II base stocks, a viscosity index improver, oxidation and corrosion inhibitors, antiwear and film strength additives, an antifoaming agent, and a pour point depressant to exceed the performance and protection requirements of most tractors and other farm equipment used in North America ¹.

INDUSTRY AND OEM SPECIFICATIONS

- ◆ JDM J20C
- ◆ API GL-4 ³
- ◆ Allison C-2, C-3 and C-4 ²

APPLICATIONS

MAJESTIC™ UHTF is a multifunctional tractor hydraulic fluid, specially formulated for use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment employing a common fluid reservoir.

FEATURES

- ✓ Excellent anti-wear capabilities
- ✓ EP & Load carrying capabilities
- ✓ Oxidation and thermal stability
- ✓ Friction durability

D1000716

5009 WEST 81ST STREET | INDIANAPOLIS | INDIANA | 46268 | 800-829-8899 | FAX 317-875-0889

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes that the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.



PRODUCT DATA SHEET

MAJESTIC™ UNIVERSAL TRACTOR HYDRAULIC FLUID (UTHF)

TECHNICAL DATA

(typical values)

SAE GRADE		10W-30
Product Number		07-392110
SDS Number		S100.1
Viscosity @ 100°C, cSt	D445	9.65
Viscosity @ 40°C, cSt	D445	63.40
Viscosity Index	D2770	134
API Gravity 60°F	D1250	32.5
Pour Point, °C	D5950	-48
Brookfield @ -35°C, cP	D2983	51,900
Color ASTM	D1500	2.0

- 1) Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices
- 2) Allison no longer recommends THF in their transmissions
- 3) API GL-4 is an automotive gear lubricant specification and this product is not recommended for use in hypoid applications

The recommended shelf life for these oils is typically 48 months from manufacturing date when stored properly in the original sealed containers.

D1000716

5009 WEST 81ST STREET | INDIANAPOLIS | INDIANA | 46268 | 800-829-8899 | FAX 317-875-0889

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes that the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.